

PERFORMANCE TABLE

Federal Hi-Shok 180-gr. JHP	Colt Anaconda	S&W 629-5	Taurus 44 CP
Average Velocity at 15 ft.	1,580 fps	1,562 fps	1,528 fps
Standard Deviation	21 fps	15 fps	22 fps
Average Muzzle Energy	999 ft-lbs	976 ft-lbs	934 ft-lbs
Smallest Group at 25 yds.	2.00 inches	2.00 inches	2.50 inches
Largest Group Size	2.50 inches	2.75 inches	3.00 inches
Average Group Size	2.18 inches	2.43 inches	2.75 inches
Remington 210-gr. SJHP			
Average Velocity at 15 ft.	1,412 fps	1,425 fps	1,384 fps
Standard Deviation	23 fps	13 fps	24 fps
Average Muzzle Energy	930 ft-lbs	948 ft-lbs	894 ft-lbs
Smallest Group at 25 yds.	2.00 inches	3.00 inches	2.75 inches
Largest Group Size	2.75 inches	3.50 inches	3.50 inches
Average Group Size	2.43 inches	3.20 inches	3.25 inches
Winchester 240-gr. HSP			
Average Velocity at 15 ft.	1,250 fps	1,259 fps	1,225 fps
Standard Deviation	22 fps	17 fps	4 fps
Average Muzzle Energy	833 ft-lbs	845 ft-lbs	800 ft-lbs
Smallest Group at 25 yds.	2.25 inches	2.00 inches	2.00 inches
Largest Group Size	2.75 inches	2.50 inches	2.75 inches
Average Group Size	2.58 inches	2.28 inches	2.48 inches

Accuracy testing consisted of five consecutive 5-shot groups with each load.
 fps=feet per second. ft-lbs=foot-pounds